



BM2 HOT AIR GENERATOR TITAN 185T (OIL-GAS)

Product price:

7.148,25 € tax excluded

Product description:

BM2 HOT AIR GENERATOR TITAN 185T (OIL-GAS)

BM2 TITAN 185T is an indirect combustion hot air generator, large size for more voluminous environments, can indifferently mount an external burner oil, LPG or methane.

BM2 TITAN 185T is equipped with a centrifugal fan that, besides being very silent, guarantees high prevalence (500 Pa), a feature that is particularly advisable for installations where long ducting is required. The combustion chamber with 5 smoke passes also guarantees a thermal efficiency of 96%.

BM2 TITAN 185T is supplied with:

Fan protection (IP 55):

- very quiet (noise ? 67 db at 2 meters);
- high prevalence and performance that ensures a high flow rate and static pressure (500 Pa) for the homogeneous and long-distance diffusion of hot air through ducts or conduits;
- fan anchored to the supporting structure by means of sturdy side members and fixing brackets;
- adjustable damper of restoration;

Rear electric control panel (IP 65):

- positioned in the rear part avoids the contact with dust, water, snow etc;
- provided with a strong metal cover that allows also the shelter of tools and documents;

Front electric service panel (IP 65):

- positioned in the front part of the machine inside the burner cover drawer: to avoid that it is in contact with dust, water, snow for an easier maintenance; for an easier control and intervention of the operator





Each main component of the BM2 TITAN 185T is equipped with quick electrical connections:

- speed of installation/disassembly and technical intervention
- elimination of installation/disassembly errors

TECHNICAL CHARACTERISTICS BM2 TITAN 185T

Phase Type: Three-phase

Fuel: Diesel - GAS

Frequency (Hz): 50

Voltage (V): 400

Nominal Thermal Power: 185.54 KW - 159563 Kcal/H - 638254 BTU/H

Power Output: 178. 12 KW - 153181 Kcal/H - 612724 BTU/H

Thermal Efficiency (%): 96

Air Flow Rate (M³/H): 16000

Available Static Pressure: 500 Pa - 50 mm H₂O

Thermal Gap At 20°C (°C): 46

Effective Working Range (M): 63

Gasoil Consumption (Kg/H): 14. 68

Methane Consumption (m³/H): 17682

Methane Feeding Pressure (mbar): 20

LPG Consumption (m³/H - Kg/H): 6981 - 13. 63

LPG Feeding Pressure (mbar): 37

Electrical Power (W): 4200

Length (mm): 2413

Width (mm): 920

Height (mm): 1620

Dry Weight (Kg): 430

Are you looking for a hot air generator with different technical characteristics? Here you can find the full range of BM2 heaters or other specialized brands.

Images and technical data are not binding and may be subject to revision by the manufacturer.

Product features:

Phase: Three phase

Fuel: Diesel - GAS

Frequency (Hz): 50

Voltage (V): 400

Rated heat power: 185.54 KW - 159563 Kcal/h - 638254 BTU/h

Output heat power: 178.12 KW - 153181 Kcal/h - 612724 BTU/h



Heat efficiency (%): 96

Air flow (m³/h): 16000

Available static press: 500 Pa - 50 mm H₂O

Temperature rise at 20°C (°C): 46

Effective heat range (m): 63

Oil consumption (Kg/h): 14.68

Natural Gas consumption (m³/h): 17.682

Inlet pressure Natural Gas (mbar): 20

LPG consumption (m³/h - Kg/h): 6.981 - 13.63

Inlet pressure LPG (mbar): 37

Power consumption (W): 4200

Ø flue (mm): 200

Ø outlet hose - L.max 1 way (mm - m): 700 - 50

Ø outlet hose - L.max 2 ways (mm - m): 500 - 30

Ø outlet hose - L.max 4 ways (mm - m): 350 - 25

Ø outlet snorkel - L.max (mm - m): 100 - 6

Ø inlet hose - L.max (mm - m): 720 - 10

Length (mm): 2413

Width (mm): 920

Height (mm): 1620

Dry weight (Kg): 430