



# BM2 HOT AIR GENERATOR GP45A



**Product price:**

**633,00 € tax excluded**

## Product description:

### BM2 HOT AIR GENERATOR GP45A

BM2 GP45A is an automatic start LPG-fuelled hot air generator, perfect for heating closed but ventilated rooms such as construction sites, greenhouses and farms.

BM2 GP45A is powered by high-pressure LPG, equipped with an integrated, direct-burning burner. The BM2 GP45A hot air generator is made with automatic ignition thanks to a flame control device, which allows the connection of a thermostat to control ignition and shutdown. For their power supply they are usually connected to LPG cylinders, which makes them handy and very economical.

The BM2 GP45A hot air generator comes complete with:

- Built-in LPG burner
- Safety thermostat
- Electronic flame control with ionization detection
- Power cord with plug
- Socket for connection to thermostat, humidistat or timer
- Complies with UNI EN 1596:2008

### TECHNICAL FEATURES BM2 GP45A

Maximum heat output: 46.73 KW / 40180 kcal/h / 159450 BTU/h

Minimum heat output: 22.76 KW / 19,570 kcal/h / 77,660 BTU/h

Power supply: LPG

Maximum gas consumption: 2,979 Kg/h

Minimum gas consumption: 1,454 Kg/h

Gas pressure: 1.5 - 0.4 bar

Efficiency: 100 %



Air flow: 1250 m<sup>3</sup>/h  
Air temperature at 20°C: 62 °C  
Electrical power: 112 W  
Voltage: 230 V  
Phase: Single phase  
Frequency: 50/60 Hz  
Width: 575 mm  
Length: 277 mm  
Height: 511 mm  
Dry weight: 13.6 Kg

Are you looking for a hot air generator with different technical characteristics? Here you can find the full range of hot air generators BM2 or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

**Product features:**

Phase: Single phase  
Fuel: LPG  
Frequency (Hz): 50 / 60  
Voltage (V): 230  
Max rated heat power: 46.73 KW - 40180 Kcal/h - 159450 BTU/h  
Min rated heat power: 22.76 KW - 19570 Kcal/h - 77660 BTU/h  
Max Gas consumption (Kg/h): 2.979  
Min Gas consumption (Kg/h): 1.454  
Gas pressure (bar): 1.5÷0.4  
Heat efficiency (%): 100  
Air flow (m<sup>3</sup>/h): 1250  
Air temperature at 20°C (°C): 62  
Power consumption (W): 112  
Length (mm): 575  
Width (mm): 277  
Height (mm): 511  
Dry weight (Kg): 13.6