



# BM2 HOT AIR GENERATOR GP85A



Product price:

**956,25 € tax excluded**

## Product description:

### BM2 HOT AIR GENERATOR GP85A

BM2 GP85A is an automatic start LPG-fuelled hot air generator, perfect for heating closed but ventilated rooms such as construction sites, greenhouses and farms.

BM2 GP85A is powered by high-pressure LPG, equipped with an integrated burner and direct combustion. The BM2 GP85A hot air generator is made with automatic ignition thanks to a flame control device, which allows the connection of a thermostat to control ignition and shutdown. For their power supply they are usually connected to LPG cylinders, which makes them handy and very economical.

The BM2 GP85A hot air generator comes complete with:

- Built-in LPG burner
- Safety thermostat
- Electronic flame control with ionization detection
- Power cord with plug
- Socket for connection to thermostat, humidistat or timer
- Complies with UNI EN 1596:2008

### TECHNICAL FEATURES BM2 GP85A

Maximum heat output: 84.81 KW / 72925 kcal/h / 289385 BTU/h

Minimum heat output: 40.95 KW / 35210 kcal/h / 139730 BTU/h

Power supply: LPG

Maximum gas consumption: 5.53 Kg/h

Minimum gas consumption: 2.458 Kg/h

Gas pressure: 1.5 - 0.4 bar

Efficiency: 100 %



Air flow rate: 2550 m<sup>3</sup>/h  
Air temperature at 20°C: 65 °C  
Electrical power: 240 W  
Voltage: 230 V  
Phase: Single phase  
Frequency: 50 Hz  
Width: 700 mm  
Length: 317 mm  
Height: 538 mm  
Dry weight: 16 Kg

Are you looking for a hot air generator with different technical characteristics? Here you can find the full range of hot air generators BM2 or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

**Product features:**

Phase: Single phase  
Fuel: LPG  
Frequency (Hz): 50  
Voltage (V): 230  
Max rated heat power: 84.81 KW - 72925 Kcal/h - 289385 BTU/h  
Min rated heat power: 40.95 KW - 35210 Kcal/h - 139730 BTU/h  
Max Gas consumption (Kg/h): 5.53  
Min Gas consumption (Kg/h): 2.458  
Gas pressure (bar): 1.5÷0.4  
Heat efficiency (%): 100  
Air flow (m<sup>3</sup>/h): 2550  
Air temperature at 20°C (°C): 65  
Power consumption (W): 240  
Length (mm): 700  
Width (mm): 317  
Height (mm): 538  
Dry weight (Kg): 16