

PRAMAC LIFTER ELECTRIC STACKER RX10/09



Product price:

4.069,00 € tax excluded

Product description:

PRAMAC LIFTER ELECTRIC STACKER RX10/09: The Ultimate Solution for Efficient Material Handling

The PRAMAC LIFTER RX10/09 represents the pinnacle of efficiency and innovation in the realm of material handling equipment. PRAMAC LIFTER RX10/09 designed with precision and built for durability, this pedestrian-operated stacker is the ideal choice for businesses seeking a reliable solution for moving and lifting loads up to 1000 Kg. Its electric drive system ensures smooth operation, while its compact design makes it suitable for a wide range of applications in both distribution and manufacturing environments.

Key Features of the PRAMAC LIFTER RX10/09:

- Electric Drive: Offers a clean, efficient power source, making it suitable for indoor use without the worry of emissions.
- Pedestrian Functioned: Ensures safety and precision in tight spaces, with the operator maintaining full control from a walking position.
- Load Capacity: Capable of handling loads up to 1000 Kg, making it versatile for various material handling tasks.
- Compact Dimensions: With an overall length of 1675 mm and width of 794 mm, this stacker can navigate narrow aisles and tight spaces with ease.
- Lifting Capabilities: Features a lift height of 810 mm, with a normal free lifting of 810 mm, allowing for efficient stacking and storage solutions.
- Ergonomic Design: The ergonomic tiller, placed laterally, enhances visibility and reduces operator fatigue, ensuring comfort and efficiency during operation.
- Versatility at Its Core:

The PRAMAC LIFTER RX10/09 is not just a stacker; it's a versatile tool designed to adapt to your material handling needs. Whether moving palletized goods horizontally or using it as an



adjustable worktable, this electric stacker reduces stress on operators and increases productivity. Its 60 mm thick forks are designed for easy entry into pallets, making it an indispensable asset for your functions.

Ergonomics and Maintenance:

Understanding the importance of operator comfort and machine upkeep, the PRAMAC LIFTER RX10/09 features an ergonomic tiller for increased visibility and easy maneuverability. The robust ABS carter/cover, complete with storage compartments, is easily removable for quick maintenance. This design philosophy extends to the battery pack, offering up to 3 hours of autonomy, with an option for a 4-hour EVO battery, ensuring your functions keep moving without interruption.

Conclusion PRAMAC LIFTER RX10/09:

The PRAMAC LIFTER ELECTRIC STACKER RX10/09 is a testament to the blend of ergonomics, versatility, and efficiency. Its robust design, coupled with easy access for maintenance, ensures low operational costs and a high return on investment. Ideal for handling goods in narrow spaces and corridors, this compact, completely electric stacker is your solution to the challenges of modern material handling. Embrace the power of the PRAMAC LIFTER RX10/09 and elevate your operational efficiency to new heights.

Conosci la gamma dei nostri prodotti di Electric Stackers.

The images are purely indicative.

Product features:

Drive: Electric

Operator type: Pedestrian

Load capacity (Kg): 1000

Load centre distance (mm): 600

Load axle to end forks (mm): 786

Wheel base (mm): 1165

Service weight (Kg): 337

Axle load, laden rear (Kg): 932

Axle load, laden front (Kg): 405

Axle load, unladen front (Kg): 240

Axle load, unladen rear (Kg): 97

Tyres: front wheels: RUBBER

Tyres: stabilizers wheels: POLY.C.

Tyres: rear wheels: POLY.C.

Diameter steering wheels (mm): 186



Width steering wheels (mm): 50
Diameter load rollers (mm): 82
Width load rollers (mm): 70
Diameter stabilizers wheels front (mm): 125
Width stabilizers wheels front (mm): 45
Quantity rear wheels: 2
Tread front (mm): 505
Tread rear (mm): 410
Height mast lowered (mm): 1270
Normal free lifting (mm): 810
Lift height (mm): 810
Height mast extended (mm): 1270
Height of tiller in drive position max (mm): 1365
Height of tiller in drive position min (mm): 930
Height lowered (mm): 90
Overall length (mm): 1675
Length to face of forks (mm): 522
Overall width (mm): 794
Thickness fork (mm): 60
Width fork (mm): 150
Length fork (mm): 1153
Fork carriage width (mm): 650
Distance between fork arms (mm): 560
Ground clearance at centre of wheelbase (mm): 20
Aisle width (mm): 2120
Turning radius (mm): 1344
Travel speed laden (Km/h): 3.7
Travel speed unladen (Km/h): 4.3
Lifting speed laden (m/s): 0.11
Lifting speed unladen (m/s): 0.18
Lowering speed laden (m/s): 0.18
Lowering speed unladen (m/s): 0.18
Max gradeability laden (%): 9
Max gradeability unladen (%): 25
Service brake: Electric
Drive motor power (KW): 0.35
Lift motor power (KW): 2.2
Battery voltage (V): 24
Battery capacity min (Ah): 70
Battery capacity max (Ah): 70
Battery weight min (Kg): 32
Battery weight max (Kg): 32
Energy consumption according to VDI cycle (KWh/h): 0.45
Sound level at driver's ear: 63
Type of lifting: Electric

