



SINCRO R80 LBL Single Phase Synchronous AC Alternator 2.2 kVA Capacitor

Product description:

SINCRO R80 LBL ALTERNATOR 2.7KVA SINGLE-PHASE

SINCRO R80 LBL singlephase alternator with a power of 2,7KVA, this unit has a Brushless operation equipped with capacitor voltage regulator.

The SINCRO R80 LBL is foreseen for the operation at frequency 50 or 60 HZ, the possibility to work on these two frequencies makes possible its application for any service voltage increasing its versatility, for the correct operation. For the correct operation it is only necessary to verify that the calibrations are correct for the intended use.

All components that make up the SINCRO R80 LBL are subjected to a specific coating and/or impregnation process to safeguard the functionality of the generator and to protect the critical peers in various conditions of use.

For extreme atmospheric conditions models are available that also guarantee the IP23 standard which provides protection against water up to 60° from the vertical. SINCRO R80 LBL is a brushless alternator, this feature combined with the high efficiency of the voltage regulator ensure a low level of interference with radio waves.

The singlephase alternator is lightweight and small in size, suitable for installation on board of compact and transportable machines, ensuring reliability and high performance.

Select the alternator that reflects the **technical specifications you require**, visit our dedicated section to understand how.

TECHNICAL FEATURES SINCRO R80 LBL

Phase Type: Single-phase





Maximum singlephase output: 2,2KW

Maximum singlephase continuous output: 1,76KW

Maximum singlephase output: 2,7KVA

Maximum singlephase continuous output: 2,2KVA

Frequency: 50-60 Hz

Voltage: 230 V

Protection class: IP23

Alternator speed: 3000 rpm

Number of poles: 2 Weight: 13. 8 Kg Width: 171 mm Length: 261 mm Height: 240 mm

Brushless

Voltage regulator: Capacitor

Type of alternator: constant speed

Looking for a product with different features? Here you can find the entire range SINCRO and other specialized brands.

Images and technical data are not binding and subject to change by the manufacturer

Product features:

Phase: Single phase Frequency (Hz): 50 Voltage (V): 230

Engine rpm (rpm): 3000

Poles: 2

Single-phase power (KW): 2.2 Single-phase power (KVA): 2.2

Efficiency (%): 73

Protection degree: IP23

Dry weight (Kg): 14

Brushes: No

Type of alternator: Constant Speed

Voltage regulator: Capacitor

