

CGM 15TRL PTO GENERATOR SINGLE- PHASE / THREE-PHASE 15 KVA AVR

Product price:

2.580,00 € tax excluded

Product description:

CGM 15TRL PTO GENERATOR SINGLE-PHASE / THREE-PHASE 15 KVA AVR

CGM 15TRL single / three-phase PTO generator with 1500 rpm tractor attachment, capable of delivering a power of 15KVA, complete with **AVR voltage regulator**.

The CGM 15TRL easy to transport, install and position thanks to its compact size, this model is ideal to be mounted on a tractor unit. The CGM 15TRL cardan generator has a required tractor power of 30 HP and a PTO speed of 430 rpm.

These compact, robust and easy-to-use generators are complete with base with 3-point hitch for secure attachment to any tractor.

Power transmission takes place via the cardan joint (not included), connected to the genset multiplier.

The generators for attachment to the tractor are mainly designed for farms, farms, livestock and mountain pastures but easily adapt to any emergency situation.

The CGM 15TRL is a professional tractor unit which makes it one of the best choices over its competitors, equipped with a sturdy structure with protective frame.

Technical characteristics CGM 15TRL:

Phase type: Single/Three-phase

Continuous power: 15 KVA

Continuous power: 12 KW

Emergency power: 16.5 KVA

Emergency power: 13.2 KW

Voltage: 230 / 400 V

Frequency: 50 Hz

Engine speed: 1500 rpm

Tractor power required: 30 hp

PTO revs: 430 rpm

Gearbox ratio: 1:3.5

Gearbox oil capacity: 0.5 Lt

Alternator: Linz, self-excited, with brushes

Socket panel: 1 x Schuko, 1 x CEE 16A 3P 230V, 1 x CEE 32A 5P 400V

Voltage regulator: AVR

Length: 1150 mm

Width: 960 mm

Height: 1030 mm

Weight: 150 Kg

Are you looking for a product with different technical characteristics? [HERE](#) you can find the entire range of CGM PTO generator or other specialized brands.

Pictures and technical data are not binding.

Product features:

Phase: Single phase / Three phase

Maximum power three phase (KW): 13.2

Continuous power three phase (KW): 12

Maximum power three phase (KVA): 16.5

Continuous power three phase (KVA): 15

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x Schuko, 1 x CEE 16A 3P 230V, 1 x CEE 32A 5P 400V

Engine rpm (rpm): 1500

Oil capacity (L): 0.5

Alternator: With brushes

Poles: 4

Protection degree: IP21

PTO speed (round/min): 430

Required tractor power: 30 HP

Transmission ratio: 1 : 3.5

Length (mm): 900

Width (mm): 850

Height (mm): 800

Dry weight (Kg): 150

Silenced: No

Super silenced: No
Voltage regulator: AVR