

# CGM 10P - APERTO CON CENTRALINA MANUALE

Product price:

**6.690,00 € tax excluded**

## Product description:

CGM 10P-B20 Single/three-phase 11KVA generator with manual control panel

The CGM 10P-B20 is a single/three phase 11KVA generator with a 1500 rpm Perkins diesel engine, compact and easy to use, mounted on a fixed base. This CGM 10P-B20 generator is in the open version and is easy to handle and transport thanks to its base with swinging feet.

The CGM 10P-B20 generator consists of a Linz, Stamford or Mecc Alte alternator, self-excited, brushless and with AVR voltage regulator. The CGM 10P-B20 generator has an electric start with battery and a low fuel consumption of only 2 litres per hour at 75% load. The fuel tank is incorporated in the crankcase for ease of use.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 10P-B20 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

## Technical characteristics of the CGM 10P-B20 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 8.8 KW / 11 KVA

Three-phase continuous power: 8 KW / 10 KVA

Maximum single-phase power: 2.9 KW / 3.67 KVA

Single-phase continuous use power: 2.67 KW / 3.3 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: PERKINS 403A-11G

Engine speed: 1500 rpm

Starting: Electric

Consumption: 2 Lt/h at 75% load

Length: 1400 mm

Width: 700 mm

Height: 1400 mm  
Weight: 360 Kg  
AVR

If you are looking for a product like the CGM 10P-B20 then you can browse the full range of CGM generators or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

**Product features:**

Phase: Single phase / Three phase  
Maximum power single phase (KW): 2.9  
Continuous power single phase (KW): 2.67  
Maximum power single phase (KVA): 3.67  
Continuous power single phase (KVA): 3.3  
Maximum power three phase (KW): 8.8  
Continuous power three phase (KW): 8  
Maximum power three phase (KVA): 11  
Continuous power three phase (KVA): 10  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: 1 CEE 5P 400V 16A + 1 CEE 3P 230V 16A  
Engine: PERKINS 403A-11G  
Emissions Regulations: Stationary Use  
Engine rpm (rpm): 1500  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 1131  
Number cylinders: 3  
Cooling: Water  
Alternator: Brushless  
Poles: 4  
Protection degree: IP44  
Bore x stroke (mm): 77 x 81  
Fuel tank capacity (L): 55  
Consumption (L/h): 2  
Running time (h): 27.5  
Length (mm): 1400  
Width (mm): 700  
Height (mm): 1400  
Dry weight (Kg): 360

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : No

Voltage regulator: AVR

Engine manufacturer: Perkins