



# CGM 12.5DE - APERTO CON CENTRALINA MANUALE



## Product description:

## Product features:

Phase: Single phase

Maximum power single phase (KW): 11

Continuous power single phase (KW): 10

Maximum power single phase (KVA): 13.75

Continuous power single phase (KVA): 12.5

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: N.1 x 230V 63A 3P CEE / N.1 x 230V 16A 3P CEE

Engine: KOHLER 25LD 425/2

Engine rpm (rpm): 3000

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 851

Number cylinders: 2

Oil capacity (L): 1.7

Cooling: Air

Alternator: Linz, brushless

Poles: 2

Protection degree: IP55

Bore x stroke (mm): 75 x 77.6

Fuel tank capacity (L): 4

Consumption (L/h): 2.8 at 75% of the load

Running time (h): 1.4

Acoustic pressure: 77 dB(A) at 7 m

Length (mm): 900



---

Width (mm): 600  
Height (mm): 750  
Dry weight (Kg): 170  
Silenced: No  
Super silenced: No  
ATS Switch device : No  
Voltage regulator: Capacitor  
Engine manufacturer: Kohler