



Genmac G2200 Gasoline Generator 2200 Watt AVR

Product description:

GENERATOR GENMAC G2200 MONOPHASE WITH AVR

The generator Genmac G2000 singlephase is powered by a gasoline engine and can deliver a continuous power of 2KW, including AVR.

The 2KW singlephase generator is equipped with high quality components, it is lightweight, compact, with a modern design and very easy to transport. The 2KW singlephase generator is equipped with a manual rope starter.

The 2KW singlephase generator has been specially developed for camping, caravans, houses, and hobby applications, etc., for this reason it reflects the peculiar features and comfort that allow its reliability and comfort in the fields of application.

The standard equipment on the Genmac G2000 generator includes a convenient **counter**, **tank** for great autonomy and **IP23 rain protection**, to use it also in case of bad weather.

The advantages of AVR voltage regulator

The automatic voltage regulator, or **AVR** allows the Genmac 2KW singlephase generator to deliver stable energy and therefore be able to connect equipment with delicate electronics such as computers, appliances, smartphones and tablets: the generator set is therefore ideal for home use, camping, hobby and leisure, but also for construction sites and craftsmen.

The AVR voltage regulator and the other quality standard of the alternator with copper windings will provide you with secure and stabilized energy.

TECHNICAL FEATURES OF THE CURRENT GENERATOR GENMAC G2000:

Power supply: Gasoline
Synchronous alternator: AVR
Singlephase
Continuous output: 2KW
Continuous output: 2KVA
Maximum output: 2. 2KW
Maximum output: 2.2KVA
Voltage: 230V
Frequency: 50Hz
Output 12V: 8 A
Protection degree: IP23
3000 rpm
Tank: 15 Lt.
Autonomy @ 75%: 8.3 h
Starting: manual recoil pad
Users: 2 schuko+thermal
1 output DC 12V + CB
Length (mm): 593
Width (mm): 475
Height (mm): 462
Dry weight (Kg): 46
Noise dB(A): 72 @ 7 m

Discover the whole range of industrial and portable power generators in the dedicated section.

Images and technical data are not binding and may be subject to revision.

Product features:

Phase: Single phase
Maximum power single phase (KW): 2.2
Continuous power single phase (KW): 2
Maximum power single phase (KVA): 2.2
Continuous power single phase (KVA): 2
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 2 SCHUKO + Thermal
Engine rpm (rpm): 3000
Ignition: Recoil
Starting system: Manual
Number cylinders: 1
Cooling: Air



Alternator: Synchronous
Protection degree: IP23
Fuel tank capacity (L): 15
Consumption (L/h): 1.8 at 75% of the load
Running time (h): 8.3 at 75% of the load
Acoustic pressure: 72 dB(A) at 7 m
Length (mm): 593
Width (mm): 475
Height (mm): 462
Dry weight (Kg): 46
Silenced: No
Super silenced: No
ATS Switch device : No
Voltage regulator: AVR

