



Genmac G5500 Gasoline Generator 5500 Watt AVR

Product price:

587,00 € tax excluded

Product description:

GENERATOR GENMAC G5500 SINGLEPHASE WITH AVR

The generator Genmac G5500 singlephase is powered by a gasoline engine and can deliver a maximum power of 5,5KW, including AVR.

The 5,5KW singlephase generator is equipped with high quality components, it is lightweight, compact, with a modern design and very easy to transport. The 5,5KW singlephase generator is equipped with a manual rope starter.

The 5,5KW singlephase generator has been specially developed for camping, caravans, houses, and hobby applications, etc., for this reason it reflects the peculiar features and comfort that allow its reliability and comfort in the fields of application.

The standard equipment on the Genmac G5500 generator includes a convenient **counter**, **tank** for great autonomy and **IP23 rain protection**, to use it also in case of bad weather.

The advantages of AVR voltage regulator

The automatic voltage regulator, or **AVR** allows the Genmac 5,5KW singlephase generator to deliver stable energy and therefore be able to connect equipment with delicate electronics such as computers, appliances, smartphones and tablets: the generator set is therefore ideal for home use, camping, hobby and leisure, but also for construction sites and craftsmen.

The AVR voltage regulator and the other quality standard of the alternator with copper windings will provide you with secure and stabilized energy.

TECHNICAL FEATURES OF THE CURRENT GENERATOR GENMAC G5500:



Power supply: Petrol
AVR Synchronous Alternator
Single-phase
Continuous output: 5KW
Continuous output: 5KVA
Maximum output: 5,5KW
Maximum output: 5,5KVA
Voltage: 230V
Frequency: 50 Hz
12V output: 8 A
Degree of protection: IP23
3000 rpm
Tank: 25 Lt.
Autonomy @ 75%: 10 h
Starting: manual recoil starter
Sockets: 2 schuko+thermal
1 DC 12V + CB
Length (mm): 684
Width (mm): 562
Height (mm): 557
Dry weight (Kg): 85
Noise level dB(A): 72 @ 7 m

Discover the whole range of industrial and portable power generators in the dedicated section.

Images and technical data are not binding and may be subject to revision.

Product features:

Phase: Single phase
Maximum power single phase (KW): 5.5
Continuous power single phase (KW): 5
Maximum power single phase (KVA): 5.5
Continuous power single phase (KVA): 5
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 2 SCHUKO + Thermal
Engine rpm (rpm): 3000
Ignition: Recoil
Starting system: Manual
Number cylinders: 1
Cooling: Air

Alternator: Synchronous
Protection degree: IP23
Fuel tank capacity (L): 25
Consumption (L/h): 2.5 at 75% of the load
Running time (h): 10 at 75% of the load
Acoustic pressure: 72 dB(A) at 7 m
Length (mm): 684
Width (mm): 564
Height (mm): 557
Dry weight (Kg): 85
Silenced: No
Super silenced: No
ATS Switch device : No
Voltage regulator: AVR