

TELWIN MOTOINVERTER 204 CE HONDA



Product description:

TELWIN MOTOINVERTER 204 CE MOTOR WELDING MACHINE 6,6KW

TELWIN MOTOINVERTER 204CE is a motor welder equipped with a Honda GX270 engine powered by gasoline, delivers a three-phase power of 6.6KW.

TELWIN MOTOINVERTER 204CE is a petrol engine driven welder with HONDA inverter technology engine with high frequency permanent magnet alternator for MMA and TIG-DC electrode welding with smear ignition.

TELWIN MOTOINVERTER 204CE allows incredible flexibility of use with a wide variety of electrodes: rutile, basic, cellulosic, stainless, cast iron, etc. It can also be used as a direct current (DC) generator for powering power tools such as drills, grinders, etc.

Features:

- 4-stroke gasoline engine with recoil start and air cooling
- Automatic block for no oil
- Motor overspeed protection
- Continuous adjustment of the welding current
- High stability of the current to variations in motor speed
- Arc force devices, hot start, anti-stick
- Welding-generator selector switch
- Thermostatic protection.

THE TECHNICAL CHARACTERISTICS TELWIN MOTOINVERTER 204CE

Phase Type: Single-Phase

Maximum Power: 6.6KW

Frequency: 50 Hz

Voltage: 230 V
Welding Current Type: DC
Welding Type: MMA / TIG
No-load Voltage: 112 V
Current Adjustment: 5-190 A
Maximum Current: 160 A
Electrode Diameter: 1.6 - 4 mm
Fuel: Gasoline
Motor: Honda GX270
Start: Manual
Length: 840 mm
Width: 470 mm
Height: 480 mm
Weight: 58 Kg

Are you looking for a welding machine with different technical characteristics? Here you can find the whole range TELWIN or other specialized brands.

Images and technical data are not binding.

Product features:

Phase: Single phase
Frequency (Hz): 50
Voltage (V): 230
Engine: Honda GX270, 4 stroke
Engine rpm (rpm): 3400
Starting system: Manual
Engine capacity (cm³): 270
Cooling: Air
Power (KW): 6.6
Protection degree: IP23
No-load voltage (V): 112
Regulation current (A): 5 - 190
Diameter electrodes (mm): 1.6 - 4
Type of welding current: DC
Type of welding: MMA / MIG
Current max (A): 160
Fuel tank capacity (L): 6
Acoustic power: 97 dB(A)
Length (mm): 840
Width (mm): 470
Height (mm): 480

Voltage regulator: Inverter
Weight (Kg): 58