



TELWIN THUNDER 304 CE KOHLER

Product description:

TELWIN THUNDER 304CE MOTORWELDING MACHINE 18,6kW

TELWIN THUNDER 304CE is a motorwelder equipped with a KOHLER CH730 engine powered by gasoline, it delivers a threephase power of 18.6kW.

TELWIN THUNDER 304CE is a gasoline engine driven welder with KOHLER CH730 inverter technology engine with high frequency permanent magnet alternator for MMA and TIG-DC electrode welding with smear ignition.

TELWIN THUNDER 304CE can be used as a singlephase and threephase AC generator to power all types of power tools (e.g. grinders, drills, dowels, breakers, etc.), compressors, neon and incandescent lighting systems, etc.

Features:

- Air-cooled 4-stroke twin-cylinder gasoline engine
- Electric start with ignition key
- Three ranges of welding current adjustment
- Three-phase 10.0 KVA socket and single-phase 4.0 KVA socket with protection
- Thermostatic protection
- Automatic low oil pressure lock
- Fuel tank with level indicator.

CARACTERISTICS:

- Three-phase 10.0 KVA socket and single-phase 4.0 KVA socket with protection
- Thermostatic protection
- Automatic low oil pressure lock
- Fuel tank with level indicator.

TECHNICAL FEATURES TELWIN THUNDER 304CE



Phase Type: Three-phase
Frequency: 50 Hz
Voltage: 400 V
Welding Current Type: DC
Welding Type: MMA
No-load Voltage: 85 V
Current Adjustment: 40 - 300 A
Max DC Current (EN 60974-1): 300 @ 35 % A
Power: 18.6kW
Mechanical Output: 25Hp
DC Current: 250 A
Electrode Diameter: 1.6 - 6 mm
Fuel: Gasoline
Motor: KOHLER CH730
Start: Electric
RPM: 3000 rpm
Protection Class: IP23
Displacement: 725 cm³
Servoir Capacity: 18 l
Acoustic Power: 78 @ 7m dB
Length: 940 mm
Width: 570 mm
Height: 790 mm
Weight: 166 Kg

Are you looking for a welding machine with different technical characteristics? Here you can find the whole range TELWIN or other specialized brands.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Frequency (Hz): 50
Voltage (V): 230 / 400
Engine: Kohler CH730, 4 stroke
Engine rpm (rpm): 3000
Starting system: Electric
Engine capacity (cm³): 725
Cooling: Air
Single-phase power (KVA): 4
Three-phase power (KVA): 10
Protection degree: IP23

No-load voltage (V): 85
Regulation current (A): 40 - 300
Diameter electrodes (mm): 1.6 - 6
Type of welding current: DC
Type of welding: MMA
Current max (A): 300
Fuel tank capacity (L): 18
Acoustic pressure: 78 dB(A) at 7 m
Length (mm): 940
Width (mm): 570
Height (mm): 790
Weight (Kg): 166