



TELWIN ELECTROMIG 400 SYNERGIC 230/400V

Product price:

2.078,00 € tax excluded

Product description:

MIG-MAG/FLUX/BRAZING/MMA and TIG DC-Lift multiprocess inverter welding machine controlled by a microprocessor, with 4-roller wire feeder.

Flexible use with various welded materials (steel, stainless steel, aluminium) or brazed materials (galvanised sheet metal). Wide variety of application fields, from industry to maintenance, installation to bodywork activities.

Synergic adjustment makes the product simple to use.

The Made in Telwin ATC technology makes it easy to achieve excellent standards of welding on thin materials thanks to state-of-the-art control of the arc.

Features:

- Manual or synergic operating;
- 40 pre-set synergic curves;
- Possibility of creating, saving and retrieving customised welding programs;
- MIG-MAG adjustments: wire up slope, electronic reactance, wire burn-back time, post gas;
- 2/4 time operation selection, Bi-Level, spot, inch and mm material thicknesses;
- Adjustments in MMA: hot start, arc force, anti-stick;
- VRD selection;
- Protections: thermostatic, overvoltage, undervoltage, overcurrent, engine driven generator (+/-15%);
- TIG Lift.

Complete with MIG-MAG torch, cable and earth clamp.

Not binding images and technical data.

Product features:

Phase: Single phase / Three phase

Frequency (Hz): 50 / 60





Voltage (V): 230 / 400

Efficiency (%): 89

Protection degree: IP23

No-load voltage (V): 106 / 73

Regulation current (A): 20 - 320 / 20 - 400

Diameter electrodes (mm): 1.6 - 8

Ø steel welding wire (mm): 0.6 - 1.6

Ø inox welding wire (mm): 0.8 - 1.6

Ø aluminium welding wire (mm): 0.8 - 1.6

Ø flux cored welding wire (mm): 1 - 1.2

Ø brazing wire (mm): 0.8 - 1.2

Type of welding: Multiprocess

MIG-MAG welding: MIG-MAG/FLUX/BRAZING

Current max (A): 320 / 400

Length (mm): 865

Width (mm): 390

Height (mm): 915

Voltage regulator: Inverter

Weight (Kg): 42

