



CGM SUPERPOWER 7000SPTE GENERATOR SINGLETHREEPHASE 7KVA

Product price:

780,00 € tax excluded

Product description:

CGM SUPERPOWER 7000SPTE GENERATOR SINGLETHREEPHASE 7KVA 5.6KW AVR

The Generator SingleThreePhase 7KVA 5,6KW CGM **SUPERPOWER 7000SPTE AVR** is with **powered by petrol** equipped with electric and manual starting, handles and wheels to carry it easily; it is a Generator SingleThreePhase 7KVA that meets a high quality standard and guarantees a high level of reliability. The whole range of Generator SingleThreePhase 7KVA has positively passed different tests for each component of which the groups and the final product are composed.

The strengths of Generator SingleThreePhase 7KVA are: the high quality of components, lightness, compactness, ease of use and also modern design. The CGM SUPERPOWER 7000SPTE is equipped with a manual rope starter.

The CGM SUPERPOWER 7000SPTE has been specially developed for camping, caravans, houses, and hobby applications etc.

The CGM Superpower 7000SPTE is equipped with a comfortable **counter**, **larger tank** for a great autonomy and **rain protection**, to use it also in case of bad weather.

The advantages of AVR voltage regulator

The automatic voltage regulator, or AVR, allows the Generator SingleThreePhase 7KVA CGM Superpower 7000SPTE to deliver stable energy and thus be able to connect equipment with delicate electronics such as computers, appliances, smartphones and tablets: the unit set is therefore ideal for home use, camping, hobby and leisure, but also for construction sites and craftsmen.

Technical Features of the Generator SingleThreePhase 7KVA CGM SUPERPOWER 7000SPTE



Maximum Power Three Phase: 5.6KW
Maximum Power Three Phase: 7 KVA
Maximum Power Single Phase: 1.87KW
Maximum Power Single Phase: 2.33 KVA
Fuel: Gasoline
Voltage: 230 V / 400 V
Frequency: 50 Hz
Motor: CGM 14. 0HP
Starting: Manual / Electrical
Consumption: 1.8 Lt/h at 75% load
Length: 717 mm
Width: 545 mm
Height: 592 mm
Weight: 70 Kg
Voltage regulator: AVR

Discover the full range of Industrial and portable current generators in the dedicated section.

Images and technical data not binding.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 1.8
Maximum power single phase (KVA): 2.3
Maximum power three phase (KW): 5.6
Maximum power three phase (KVA): 7
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: 1 x 400V - 1 x 230V
Engine: CGM 14.0HP, 4 stroke
Emissions Regulations: Stationary Use
Engine rpm (rpm): 3000
Starting system: Manual / Electric
Engine capacity (cm³): 420
Number cylinders: 1
Alternator: Copper
Fuel tank capacity (L): 25
Consumption (L/h): 1.8
Running time (h): 13.89
Acoustic pressure: 70 dB(A) at 7 m
Length (mm): 717

Width (mm): 545
Height (mm): 592
Dry weight (Kg): 70
Silenced: No
Super silenced: No
Product type: Generator
ATS Switch device : No
Voltage regulator: AVR
Engine manufacturer: CGM