

## MARINE GENSET KOHLER 5EFKOD Single-Phase 5 kVA

## Product description:

Ø.

Super-silenced single-phase KOHLER 5EFKOD marine generator 5 KVA AVR

KOHLER 5EFKOD 5 KVA marine generator with 1500 rpm engine. The KOHLER 5EFKOD is built with a soundproof enclosure that makes it supersilenced. The KOHLER 5EFKOD marine generator is built with a 3-cylinder, 4-cycle, diesel-powered Kohler engine, closed cooling system with heat exchanger. The alternator of the KOHLER 5EFKOD marine generator is with AVR voltage regulator and water cooling. With its small size, the 5EFKOD marine generator is also suitable on boats of various sizes.

## Main technical features of this nautical generator:

Phase Type: SinglePhase Power Supply: Diesel Frequency: 50 Hz Singlephase continuous power: 5 kW Singlephase continuous power: 5 kVA Voltage: choice of 115/230V, 230V or 240V KoHLER 3-cylinder engine Displacement: 1028 cc. Revolutions per minute: 1500 Liquid cooling Consumption at 75%: 1.5 L per minute Length: 780 mm Width: 528 mm Height: 559 mm Dry weight: 218 Kg

Features of the KOHLER 5EFKOD

- 12-pole connector with remote start

- Class H insulation
- Multi-voltage adjustability
- Voltage adjustment of 1.0%.
- Radio suppression

Engine features of the KOHLER 5EFKOD

- Diesel

- Certified by the Environmental Protection Agency (EPA) to meet Tier III marine auxiliary standards (60 Hz model only)

- Three cylinders
- Four cycles
- Closed cooling system
- Heat exchanger
- Lifting eye
- -. Low oil pressure shutdown
- High temperature engine shutdown
- Low seawater pressure shutdown
- Vibromount
- Belt guard
- Disposable oil filter
- Oil drain valve
- Disposable fuel filter

Features of the KOHLER 5EFKOD alternator

- - Statically excited rotating field design allows power to be obtained from stationary conductors.
- Windings are vacuum-impregnated with epoxy paint for reliability and long life.
- Rotors are dynamically balanced to minimize vibration.

- Copper windings ensure minimal heat buildup. Insulation meets NEMA standards for Class H insulation.

- Connected directly to the motor, the generator features sealed precision ball bearings with a precision machined steel sleeve in the end bracket to prevent shaft misalignment and extend bearing life.

- Mounted on a drip tray.
- Equipped with a four-conductor reconnectable stator.

Other marine generators such as the KOHLER 5EFKOD can be found by browsing the entire catalog of marine generators.

Pictures and technical data are not binding.

R

## **Product features:**

R

Phase: Single phase Continuous power single phase (KW): 5 Continuous power single phase (KVA): 5 Fuel: Diesel Frequency (Hz): 50 Engine: 4 stroke Engine rpm (rpm): 1500 Speed governor: Mechanical Starting system: Electric Engine capacity (cm<sup>3</sup>): 1028 Number cylinders: 3 Oil capacity (L): 2.5 Cooling: Water Poles: 4 Bore x stroke (mm): 75 x 77.6 Compression ratio: 24.5 : 1 Motor insulation class: H Length (mm): 780 Width (mm): 528 Height (mm): 559 Dry weight (Kg): 218 Silenced: Yes Super silenced: Yes Product type: Generator Voltage regulator: Digital AVR Engine manufacturer: Kohler