



# KOHLER 16 EKOZD Marine Genset 15 kVA



## Product description:

Super-silenced single-phase KOHLER 16EKOZD marine generator 15 KVA AVR

Kohler 16EKOZD Marine generator single phase 15 KVA with 1800 rpm motor EPA certified. The KOHLER 16EKOZD single-phase marine generator is built with a soundproof enclosure that makes it **supersilenced**. The KOHLER 16EKOZD single-phase marine generator is built with a 4-cylinder, 4-cycle Kohler diesel-powered engine, closed cooling system with heat exchanger. The alternator of the single-phase KOHLER 16EKOZD marine generator is brushless with **AVR** voltage regulator and water-cooled.

## Features of the KOHLER 16EKOZD marine generator

- Class H insulation
- Multi-voltage adjustability
- Voltage adjustment of 1.0%.
- Radio suppression

## Engine features of the KOHLER 16EKOZD marine generator

- Diesel
- Environmental Protection Agency (EPA) certified for compliance with Tier III marine auxiliary standards
- Four cylinders
- Four cycles
- Closed cooling system
- Heat exchanger
- Electric fuel lift pump
- Lifting eyelet
- Low oil pressure shutdown
- High temperature engine shutdown



- Low seawater pressure shutdown
- Vibromount
- Belt guard
- Disposable oil filter
- Oil drain valve
- Disposable fuel filter

#### TECHNICAL FEATURES KOHLER 16EKOZD

Phase Type: Single-Phase  
Maximum Single-Phase Power: 15 KW  
Fuel: Diesel  
Frequency: 60 Hz  
Voltage: 120/240 V  
Motor: Kohler  
Emissions Regulation: EPA  
Engine RPM: 1800 rpm  
Length: 1064 mm  
Width: 652.5 mm  
Height: 711 mm  
Dry Weight: 393 Kg

Other marine generators such as the KOHLER 16EKOZD can be found by browsing the entire catalog of marine generators.

Pictures and technical data are not binding.

#### **Product features:**

Phase: Single phase  
Continuous power single phase (KW): 15  
Continuous power single phase (KVA): 15  
Fuel: Diesel  
Frequency (Hz): 60  
Engine: Kohler  
Emissions Regulations: EPA  
Engine rpm (rpm): 1800  
Speed governor: Mechanical  
Engine capacity (cm<sup>3</sup>): 1900  
Number cylinders: 3  
Cooling: Water  
Bore x stroke (mm): 88 x 102  
Compression ratio: 17 : 1



---

Motor insulation class: H  
Consumption (L/h): 3.51 at 75% of the load  
Length (mm): 1064  
Width (mm): 652.5  
Height (mm): 711  
Dry weight (Kg): 393  
Silenced: Yes  
Super silenced: Yes  
Type of combustion: Direct  
Voltage regulator: AVR  
Engine manufacturer: Kohler

