



KOHLER 24 EKOZD Single-phase 24 kVA 60 Hz Marine Generator Set

Product description:

Super-silenced single-phase KOHLER 24EKOZD marine generator 24 KVA AVR

Kohler 24EKOZD single phase 24 KVA marine generator with 1500 rpm motor. The KOHLER 24EKOZD single-phase marine generator is designed with a soundproof enclosure that makes it **supersilenced**. The KOHLER 24EKOZD single-phase marine generator is designed with a 4-cylinder, 4-cycle Kohler diesel engine, closed cooling system with heat exchanger. The alternator of the single-phase KOHLER 24EKOZD marine generator is brushless with **AVR** voltage regulator and water-cooled.

Here are the main technical data of the 24EKOZD generator:

Phase Type: Single Phase

Single Phase Continuous Power: 24 KW

Single Phase Continuous Power: 24 KVA

Fuel: Diesel

Frequency: 60 Hz

Voltage: 120 V or 120/240 V

Motor: Kohler

Motor RPM: 1800 rpm

Length: 1197 mm

Width: 652.5 mm

Height: 711 mm

Dry weight: 471 Kg

Features of the KOHLER 24EKOZD

- Class H insulation
- Multi-voltage adjustability
- Voltage adjustment of 1.0%.
- Radio suppression

Engine features of the KOHLER 24EKOZD

- Diesel
- Environmental Protection Agency (EPA) certified for compliance with Tier III marine auxiliary standards (60 Hz model only)
- Four cylinders
- Four cycles
- Closed cooling system
- Heat exchanger
- Electric fuel lift pump
- Lifting eyelet
- Low oil pressure shutdown
- High temperature engine shutdown
- Low seawater pressure shutdown
- Vibromount
- Belt guard
- Disposable oil filter
- Oil drain valve
- Disposable fuel filter

Features of the KOHLER 24EKOZD

- Brushless rotating field design allows power to be obtained from stationary conductors.
- Windings are vacuum-impregnated with epoxy paint for reliability and long life.
- Rotors are dynamically balanced to minimize vibration.
- Copper windings ensure minimal heat buildup. Insulation meets NEMA standards for Class H insulation.
- Connected directly to the motor, the generator features sealed precision ball bearings with a precision machined steel sleeve in the end bracket to prevent shaft misalignment and extend bearing life.
- Mounted on a drip-proof tray.
- Equipped with a four-conductor reconnectable stator.
- Capable of withstanding a line-to-neutral short-circuit current of up to 300% of rated current for up to 2 seconds. (Short-circuit performance IEC 60092-301).

You can find other marine generators such as the KOHLER 24EKOZD with different technical features on our catalog of marine generators.

Non-binding images and technical data.

Product features:

Phase: Single phase



Continuous power single phase (KW): 24
Continuous power single phase (KVA): 24
Fuel: Diesel
Frequency (Hz): 60
Engine: Kohler
Engine rpm (rpm): 1800
Speed governor: Mechanical
Engine capacity (cm³): 2500
Number cylinders: 4
Cooling: Water
Bore x stroke (mm): 88 x 102
Compression ratio: 17 : 1
Motor insulation class: H
Consumption (L/h): 5.26 at 75% of the load
Length (mm): 1197
Width (mm): 652.5
Height (mm): 711
Dry weight (Kg): 471
Silenced: Yes
Super silenced: Yes
Type of combustion: Direct
Product type: Generator
Voltage regulator: AVR
Engine manufacturer: Kohler